

**GRIZZLY ALX — ALL ALUMINUM**

**Haulmark®**

## **THE BENCHMARK IN TOUGHNESS & LOW MAINTENANCE**

If you've got a job to do, the Haulmark® **GRIZZLY ALX** is the way to do it. All Aluminum construction delivers a lighter trailer for better fuel economy and increased hauling capacity. The Haulmark® **GRIZZLY ALX** won't rust even on the saltiest roads, so your trailer will keep looking great job after job, year after year. Beauty and brawn in one easy-to-tow, lightweight package!



*Trailer shown may feature optional equipment available at an additional charge.*

**GRIZZLY ALX**  
ALL ALUMINUM

# SPECIFICATIONS

**GRIZZLY ALX**  
ALL ALUMINUM

|   | GRALX714T2*           | GRALX716T2*           | GRALX8516T2*          | GRALX8520T2*          | GRALX8524T3           |
|---|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| <b>Body:</b> Length (Including "V")       | 17'0"                 | 19'0"                 | 19'0"                 | 23'0"                 | 27'0"                 |
| Width                                     | 7'0"                  | 7'0"                  | 8'4"                  | 8'4"                  | 8'4"                  |
| <b>Overall:</b> Length                    | 19'4"                 | 21'4"                 | 21'4"                 | 25'4"                 | 29'4"                 |
| Width                                     | 8'6"                  | 8'6"                  | 8'6"                  | 8'6"                  | 8'6"                  |
| Height                                    | 8'4"                  | 8'4"                  | 8'6"                  | 8'6"                  | 8'7"                  |
| <b>Interior:</b> Length                   | 16'7"                 | 18'7"                 | 18'7"                 | 22'7"                 | 26'7"                 |
| Width                                     | 6'9"                  | 6'9"                  | 8'1"                  | 8'1"                  | 8'1"                  |
| Height                                    | 6'6"                  | 6'6"                  | 6'6"                  | 6'6"                  | 6'6"                  |
| <b>Platform Height</b>                    | 19"                   | 19"                   | 21"                   | 21"                   | 21"                   |
| <b>Axles:</b> Suspension                  | Dexter® Torflex       | Dexter® Torflex       | Dexter® Torflex       | Dexter® Torflex       | Dexter® Torflex       |
| Quantity                                  | Tandem                | Tandem                | Tandem                | Tandem                | Tandem                |
| Start Angle                               | 10° Up                | 10° Up                | 10° Up                | 10° Up                | 10° Up                |
| <b>Electric Brakes with Breakaway Kit</b> | 4-Wheel Electric Drum | 4-Wheel Electric Drum | 4-Wheel Electric Drum | 4-Wheel Electric Drum | 4-Wheel Electric Drum |
| <b>Radial Tire Size</b>                   | ST205/75R15           | ST205/75R15           | ST205/75R15           | ST205/75R15           | ST225/75R15           |
| Tire Load Range                           | C                     | C                     | C                     | C                     | D                     |
| <b>Hitch Ball Size</b>                    | 2½"                   | 2½"                   | 2½"                   | 2½"                   | 2½"                   |
| <b>Hitch Height to Top of Ball</b>        | 17" to 21"            | 17" to 21"            | 19" to 23"            | 19" to 23"            | 19" to 23"            |
| <b>Hitch Weight (% of Curb Weight)</b>    | 10% - 15%             | 10% - 15%             | 10% - 15%             | 10% - 15%             | 10% - 15%             |
| <b>GVWR</b>                               | 7,000 lbs.            | 7,000 lbs.            | 7,000 lbs.            | 7,000 lbs.            | 9,990 lbs.            |
| <b>Curb Weight (Approximate)</b>          | 2,045 lbs.            | 2,150 lbs.            | 2,610 lbs.            | 3,010 lbs.            | 3,700 lbs.            |
| <b>Payload Capacity (Approximate)</b>     | 4,955 lbs.            | 4,850 lbs.            | 4,390 lbs.            | 3,990 lbs.            | 6,290 lbs.            |
| <b>Rear Door Opening - Width x Height</b> | 76" x 72"             | 76" x 72"             | 92" x 72"             | 92" x 72"             | 92" x 72"             |
| <b>Side Door Width</b>                    | 36"                   | 36"                   | 36"                   | 36"                   | 36"                   |
| <b>Tube Main Rails</b>                    | 2" x 4"               | 2" x 4"               | 2" x 6"               | 2" x 6"               | 2" x 6"               |
| <b>12v Trailer Plug Connection</b>        | 7-Way                 | 7-Way                 | 7-Way                 | 7-Way                 | 7-Way                 |

\*Available in 9,990 lb. GVWR

## STANDARD FEATURES

- DuraCage™ Aluminum Construction
  - Aluminum Tube Main Rails
  - 16" OC Floor Crossmembers (Full Height of Main Rail)
  - 16" OC Tube Vertical Posts
  - 16" OC Tube Roof Bows
  - Dust-Proof Sidewalls
- All-Aluminum Hardware
- Adjustable Height 2-5/16" Wallace Forge® Cast Coupler
- 8,000 lb. Dropleg Sidewind Jack with Footplate
- Dexter® Torflex Axles with EZ-Lube® Hubs
- Radial Tires with Silver Viper Aluminum Wheels
- 3/4" PlexCore™ High-Performance Floor & Ramp Decking
- 3/8" PlexCore™ High-Performance Interior Sidewall Liner
- 5,000 lbs. D-Rings (4)
- Sidewall Vents
- 12v High Output LED Dome Lights with Switch (800 Lumens)
- .030 Aluminum Exterior — Bonded For Smooth Appearance
- Thick, Bold Extruded Aluminum Top/Bottom Trim
- 1-Piece Aluminum Roof
- Smooth Aluminum Fenderettes
- 24" ATP Stoneguard
- Heavy-Duty 36"W Side Door with Flush Lock & Dead Bolt (1½" Core)
- Double Rear Doors (Rear Ramp Door Optional)
- 12v Clear Lens LED Slim Line Tail Lights
- 12v Clear Lens LED Clearance Lights
- Rear ID Bar with Built-In Loading Light with Switch
- 3-Year Limited Warranty



Shown with optional rear ramp door available at additional charge



Silver Viper Aluminum Wheels & Heavy-Duty Side Door Standard



GET MORE | GO FURTHER

www.haulmark.com

Specifications, features, options, packages & pricing subject to change **without** notice. Contact your authorized Haulmark® dealer for more information.